



US009638351B2

(12) **United States Patent**
Ardavanis

(10) **Patent No.:** **US 9,638,351 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **VESSEL WITH STINGER HANDLING SYSTEM**

(71) Applicant: **Petrofac Services Ltd**, London (GB)

(72) Inventor: **Kimion Tullio Ardavanis**, Sharjah (AE)

(73) Assignee: **Petrofac Services Ltd.**, London (GB)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/039,465**

(22) PCT Filed: **Nov. 26, 2014**

(86) PCT No.: **PCT/EP2014/075676**

§ 371 (c)(1),

(2) Date: **May 26, 2016**

(87) PCT Pub. No.: **WO2015/078918**

PCT Pub. Date: **Jun. 4, 2015**

(65) **Prior Publication Data**

US 2016/0377196 A1 Dec. 29, 2016

(30) **Foreign Application Priority Data**

Nov. 26, 2013 (GB) 1320842.6

(51) **Int. Cl.**

B63B 35/03 (2006.01)

F16L 1/225 (2006.01)

B66C 23/52 (2006.01)

(52) **U.S. Cl.**

CPC **F16L 1/225** (2013.01); **B63B 35/03** (2013.01); **B66C 23/52** (2013.01)

(58) **Field of Classification Search**

CPC ... F16L 1/225; F16L 1/18; F16L 1/205; F16L 1/202; F16L 1/235; B63B 35/03; B63B

27/36; B66C 23/52

USPC 405/158, 166, 168.1; 212/307

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,257,718 A * 3/1981 Rosa B63B 35/03 114/265

5,011,333 A * 4/1991 Lanan F16L 1/23 405/166

7,328,811 B2 * 2/2008 Roodenburg B66C 13/06 212/232

2010/0189513 A1 * 7/2010 Alloggio B63B 35/03 405/166

2011/0031205 A1 * 2/2011 Roodenburg B66C 13/06 212/309

2011/0052324 A1 * 3/2011 Bruschi B63B 35/03 405/166

(Continued)

Primary Examiner — Sunil Singh

Assistant Examiner — Carib Oquendo

(74) *Attorney, Agent, or Firm* — NLO N.V.; Minerva Rivero; Catherine A. Schultz

(57) **ABSTRACT**

A pipelay vessel has a crane having a base with a hollow interior and a stinger handling system for handling a stinger extending from the side of the vessel. The stinger handling system has a link extending out through an opening from the hollow interior towards the side of the vessel for connection to the stinger. The link is arranged to transmit both tensile and compressive loading. A jack structure, located within the hollow interior of the crane base is mounted to extend and retract the link from within the crane base to raise and lower the stinger. A universal coupling may be provided for self aligning the link to the stinger in the horizontal plane.

20 Claims, 8 Drawing Sheets

